

AUTOMATIC PANEL CLAMP PNEUMATIC PANEL CLAMP

FOR FABRICATING PANELS & STAIR TREAD BLANKS
(CONCEPT BY STILLWELL STAIRBUILDERS; DESIGN & MFG BY CORDES MACHINE)

DATA SHEET
PANEL CLAMP-IT™

Model 244

The **Panel Clamp-It™** is the roughest and toughest yet most precise panel clamp available.

SIMPLE OPERATION

1. Operate dual knobs to open clamp.
2. Load boards, add glue as you go.
3. Operate dual knobs to automatically lock clamp.
4. Complete panel assembly with pipe clamps as needed.
5. Operate dual knobs to open clamp and slide out finished panel for glue drying.

FEATURES

- Super heavy duty steel construction
- Operator choice of panel width
- Standard panels squared accurately
- Rigid and square clamp arms
- Full clamping power on every panel
- Completely pneumatic
- Minimal operator training required
- Easy to load and unload
- Rugged squaring stops (no loose pieces)
- No hand adjustments required
- Available widths unlimited
- Multiple clamping stations for flexibility
- Lifetime Construction



MODEL 244 SHOWN
WITH OPTIONAL CASTERS
AND PIPE CLAMPS

DESIGN ADVANTAGES

Positive clamping (will not move when pipe clamps are on).
Maintain flat panels from end to end and side to side.
Standard widths available.
Every panel comes out square and true.
Adjustable work height (without casters).
No extra man power or hammers needed - ever.
Large clamping range (24" x 4').
Slide completed panels out easily.
Clamp up to 3-1/4" thick panels.

AVAILABLE OPTIONS

24" Deep x 4' Wide (shown above)
24" Deep x 6' Wide
24" Deep x 8' Wide
Custom Depths and Widths
Pipe Clamps With Pipe
Casters For Mobility In Small Shops

SPECIFICATIONS

Footprint w/o Overhang (Model 244)	43" w x 28" d
Height (Minimum Overall)	54"
Weight (Model 244)	800 lbs
Working Height (Adjustable)	34" - 38"
Air Required	80 psi clean and dry
Clamp Support Rail Width	1" each station

MADE
IN THE
U.S.A.

CORDES MACHINE DIVISION
REMINGTON INDUSTRIES, INC.
Leaders In Stair Machinery
269 Sheffield Street Mountainside, NJ 07092
WWW.STAIREQUIPMENT.COM
(908) 233-2600

